

# **SAFETY DATA SHEET**

Product name: Li-D-970P

Company name: NEP Inc.

Address: VORT KUDAN 3F, 3-7-14 KUDAN MINAMI, CHIYODAKU, TOKYO 102-0074, JAPAN

TEL: +81-3-3263-6741,(Emergency TEL(Kunio Masaoka Handy Phone): +81-90-6027-0828)

FAX: +81-3-3263-6741

This battery pack contains below mentioned materials. Detailed document number is ST240101036-2

general name	CAS No.	concentration (%)
Lithium Cobalt Oxide(LiCoO2)	12190-79-3	36
Alminium Foil(AI)	7429-90-5	10
Graphite(C)	7782-42-5	20
Cooper Foil(Cu)	7440-50-8	10
Other	9003-55-8	24

### Transport information

UN No.	proper shipping name	class
3480 (965)	Lithium-ion battery	9

VORT KUDAN 3F, 3-7-14 KUDAN MINAMI, CHIYODAKU, TOKYO 102-0074, JAPAN

NEP Inc.



Company name: NEP Inc.

Address: VORT KUDAN 3F, 3-7-14 KUDAN MINAMI, CHIYODAKU, TOKYO 102-0074, JAPAN

TEL: +81-3-3263-6741,(Emergency TEL(Kunio Masaoka Handy Phone): +81-90-6027-0828)

FAX: +81-3-3263-6741

## PRODUCT INTRODUCTION SHEET

Brand: NEP Inc.

Model: Li-D970P

Cell: Li-ion

Type: DV Li-ion Battery

Voltage: 7.2V

Capacity: Typical ---10.4Ah /75Wh
Built-in: 1pcs\* Power indicaror

Suggest operating temperature:  $-20^{\circ}$  C~  $+55^{\circ}$  C

Dimension: 71(W) X 39 (L) X 70(D)mm( $\pm 1$ mm)

Weight: Approximately 321g
Short circuit protection: Built-in recoverable PCB

Cut-off voltage: 6.0 V

(Test data of lab, different camera will have different running time

based on its own cut-off voltage)

Charging voltage: 8.4 V

Transportation: The aggregate equivalent lithium content: 6.4g, compliance to IATA.

(Seal, separate and keep in strong packaging during transportation.)

Maximum load: 30W

#### Charging time by Beillen chargers (full charge):

CHDV-S4-F970: Approx.310 min. CHDV-S2-F970: Approx. 340 min.

#### Remarks:

- \* It is compatible with all professional video cameras using V-lock battery packs.
- \* This model is specially designed for overseas market only.
- \* After 600 charge/discharge cycles, it is normal if the remaining capacity is lower than 60% of initial capacity. Life cycle test conditions:
  - Temperature: 2±2°C
  - Relative humidity: 65%±5.
  - Atmospheric pressure: 86 Kpa ~ 106Kpa
  - Measure the remaining capacity after 300 charge/discharge cycles at 0.5C with cut-off voltage set to 6.0V.



Company name: NEP Inc.

Address: VORT KUDAN 3F, 3-7-14 KUDAN MINAMI, CHIYODAKU, TOKYO 102-0074, JAPAN

TEL: +81-3-3263-6741,(Emergency TEL(Kunio Masaoka Handy Phone): +81-90-6027-0828)

FAX: +81-3-3265-1297

# Lithium ion Battery Test Summary(Certificate of UN test)

model

Li-D970P

Manufactuer/Brand

NEP Inc.

Address

VORT KUDAN 3F, 3-7-14 KUDANMINAMI, CHIYODAKU, TOKYO,

102-0074, JAPAN

+81-3-3263-6741

Tel e-mail

k-masaoka@nepinc.co.jp

**URL** 

https://nepinc.co.jp

**Test Laboratory** 

Shanghai Research Institute Industry Testing Co., Ltd.

Address

No.345 East Yunling Road, Shanghai, 200062, CHINA

TEL

+86-021-3176555

e-mail

zmh@ghs.cn

**URL** 

www.ghs.cn

Document Number

1119120286

Date of Test

2020-01-19

Description of Product

Lithium ion Rechargeable Battery

Normal Voltage

7.2V

Capacity(mAh/Wh)

10.4Ah / 75Wh

Lithium Equivalent Content

6.4g

Product Weight

321g

#### Test Result

No.	Name of Test	Test Result	NOTE	
T1	AltitudeSimulation	Pass	First Cycle Fully charged	After 50 Cycle Fully charged
T2	Thermal Test	Pass	4 batteries	4 batteries
T3	Vibration	Pass		
T4	Shock	Pass		
T5	External Short Circuit	Pass		
T6	Impact	Pass	First Cycle 50% charged 5cells	
T7	Overcharge	Pass	First Cycle Fully charged 4 batteries	After 50 Cycle Fully charged 4 batteries
T8	Forced Discharge	Pass	First Cycle Fully Discharged 10 cells	After 50 Cycle Fully Discharged 10 cells

Assembled Batttery Test

Not applicable

Refernce Edition

UN Manual of Tests and Criteria, ST/SG/AC. 10/11/Rev. 6 PartIII, Sub-section 38.3

Signature

Kunio Masaoka(Sales Manager)

Curio Masgoka

Sales and Marketing Div.

NEP Inc.



Company name: NEP Inc.

Address: VORT KUDAN 3F, 3-7-14 KUDAN MINAMI, CHIYODAKU, TOKYO 102-0074, JAPAN

TEL: +81-3-3263-6741,(Emergency TEL(Kunio Masaoka Handy Phone): +81-90-6027-0828)

FAX: +81-3-3263-6741

# 1.2m Drop Test Report

model

Li-D970P

Brand/Manufactuer

NEP Inc.

Address

VORT KUDAN 3F, 3-7-14 KUDANMINAMI, CHIYODAKU, TOKYO,

102-0074, JAPAN

Tel

+81-3-3263-6741

e-mail

k-masaoka@nepinc.co.jp

URL

https://nepinc.co.jp

Test Laboratory

Shenzhen Beihang Technology Co., Ltd.

Address

Room 202, 2/F, Building F, HaoWei Industrial Park, QingSong West

Road, PingShan District, Shenzhen, Guangdong, China

Document Number

ST240101036-2

Date of Test

2024-01-04

**Battery Specification** 

Description of Product	Lithium ion Rechargeable Battery
Normal Voltage	7.2V
Capacity(mAh/Wh)	10500mAh/75Wh
Lithium Equivalent Content	6.4g
Product Weight	321g

#### Test Result

Inspection method and Procedure	IATA Dangerous Goods Regulation(DGR)62th Edition
Shipping name	Lithium ion Batteries
Class or Division	9
UN number	UN3480
Packing requirements	The goods are packing according to Packaging Instruction 965 section IA
Perfomance requirements	Packing Group II
UN Packing Code/Group (Box)	4G/Y
Packing information	Size:360x360x360mm
	Battery Net Weight:0.4kg
	Battery number:2pcs

We declare that above-mentioned test is passed.

Signature

Kunio Masaoka(Sales Manager)

Kunio Masaoka

Sales and Marketing Div.

NEP Inc.



# MSDS Report MSDS 报告

Applicant's name 委托方名称	NEP Inc. エヌ・イー・ピー株式会社	
Applicant's Address 委托方地址	VORT KUDAN 3F, 3-7-14 KUDANMINAMI, CHIYODAKU, TOKYO, 102-0074, JAPAN 東京都千代田区九段南3-7-14 VORT九段3階	
Name of Sample 样品名称	Camera Li-ion Battery	
Model 型号	Li-D970P	
Nominal Voltage 标称电压	7.2V	
Rated Capacity 额定容量	10.4Ah, 75Wh	
Weight 重量	334g	
Size 尺寸 (L×W×T)	71×39×70mm	
Prepared By 编制单位	Shenzhen Beihang Technology Co., Ltd. 深圳市北航检测有限公司 Room 202, 2/F, Building F, HaoWei Industrial Park, QingSong West Road, PingShan District, Shenzhen, Guangdong, China 广东省深圳市坪山区青松西路豪威工业园 F 栋 2 楼 202 房	
Report No. 报告编号	ST240101036-2	
	Asinang Tear	

Written by 编写:	Canday	Approved by 批准:	HAVIO
• *** -			
Inspected by 审核:	Harry	Effective Date 生效日期	20 M 01 04



# Material Safety Data Sheet 化学品安全技术说明书

Section 1- Chemical Product & Company Identification 第一部分 化学品及企业标识	
Name of Sample 样品名称	Camera Li-ion Battery
Manufacturer's name 制造商名称	NEP Inc. エヌ・イー・ピー株式会社
Manufacturer's Address 生化花菇椒椒	VOORT KUDAN 3F , 3-7-14 KUDANMINAMI , CHIYODAKU , TOKYO , 102-0074 , JAPAN
制造商地址 Contact Person 联系人	東京都千代田区九段南3-7-14 VORT九段3階  Kunio Masaoka
Tel 电话	81-332636741
Emergency Tel 应急电话	81-9060270828
E-mail 邮箱	k-masaoka@nepinc.co.jp

Section 2- Hazar 第二部分 危险性	
Classification of Danger 危险性类别	See section 14. 见第十四部分。
Primary Route(s) of Exposure 浸入途径	Eye, skin contact, ingestion. 眼睛,皮肤接触,摄入。
Health Hazard 健康危害	The batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's Hazard of rupture, fire, heat, leakage of internal components, which could cause casualty loss. Abuses including but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.  正常条件下根据制造商的说明使用电池不会产生危害。使用不当的情况下,有破裂、起火、发烫、内部成分泄漏的危险,并可能造成意外损失。使用不当的行为包括但不限于下列情况:长时间充电、短路、投入火中、硬物撞击、尖物刺破、破碎,和破
	限 J 下列 同 机: 区 的 问 允 电 、



Section 3- Composition/Information on Ingredients 第三部分 成分/组成信息		
Chemical Name 化学名称	Concentration or concentration ranges (%) 浓度或浓度范围(%)	CAS Number CAS 号(化学文摘索引登记号)
Positive electrode: Lithium transition metal oxidate(Li[M]m[O]n*2)	20~60	12190-79-3 12031-65-1 12057-17-9 182442-95-1 207803-51-8
Positive electrode's base: Aluminum	1~10	7429-90-5
Negative electrode: Carbon	10~30	7782-42-5 7440-44-0
Negative electrode's base: Copper	1~15	7440-50-8
Electrolyte: Ethyl methyl carbonate Diethyl carbonate Ethylene carbonate Lithium hexafluorophosphate	5~25	623-53-0 105-58-8 96-49-1 21324-40-3
Outer case: Aluminum, Iron, aluminum laminated plastic	1~30	7429-90-5 7439-89-6

Labeling according to EC directives.

标签根据 EC 指令。

No symbol and Hazard phrase are required.

不需要象形符号和危险短语。

Note: CAS number is Chemical Abstract Service Registry Number.

注意: CAS 号是化学文摘服务注册号码。

N/A=Not apply. N / A =不适用。

Section 4- First A 第四部分 急救措	
Eye 眼睛	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.  万一接触,立即用大量的清水冲洗至少 15 分钟,翻起上下眼睑,直到化学的残留物消失为止,迅速就医。
Skin 皮肤	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid. 万一接触,用大量水冲洗至少 15 分钟,同时除去污染的衣物和鞋子,迅速就医。
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.



吸入	立即从暴露处移至空气清新处,如果呼吸困难给予输氧,立即就医。	
Ingestion	Ingesting damaged batteries, do not induce vomiting or give food or drink. Seek medical attention immediately.	
食入	食入损坏的电池,不要催吐且不要再吃下食物或喝饮料,立刻就医。	

Section 5- Fire Fighting Measures 第五部分 消防措施		
Characteristics of Hazard 危险特性	Dusts at sufficient concentrations can form explosive mixtures with air. Combustion generates toxic fumes. 高密度粉尘遇空气会形成爆炸性混合物。燃烧生成有毒烟雾。	
Hazardous Combustion Products 燃烧产生的危险物 品	Carbon dioxide. 二氧化碳。	
Fire-extinguishing Methods and Extinguishing Media 灭火方法及灭火剂	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam. 对于小型火险,可使用水枪,干冰(也就是液态二氧化碳)或化学泡沫。	
Attention in Fire- extinguishing 灭火注意事项	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. 因为压强关系,要穿戴可呼吸式全身防护装备,MSHA/NIOSH(经认证或等效的),以及佩戴全套防护装置。	

Section 6- Accidental Release Measures 第六部分 泄露应急处理		
Personal Precautions, protective equipment, and emergency procedures 个人预防措施、防护装备和应急程序	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.  万一破裂。注意! 腐蚀性物质。避免接触皮肤,眼睛或衣服。确保空气流通。根据需要使用个人防护装备。将人员撤离到安全区域。让人们远离溢出/泄漏处和处于逆风。参考第七部分和第八部分中列出的防护措施。	
Environmental Precautions 环境保护措施	Prevent product from contaminating soil and from entering sewers or waterways. 防止产品污染土壤和进入下水道或水道。	
Methods and materials for Containment 方法和材料控制	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.	



		出于安全,阻止泄漏,可以用干砂或泥土来遏制液体 溢出,立即清理溢出物。
	Methods and materials for cleaning up 清理的方法和材料	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.
		用惰性吸收剂(干砂或泥土)吸收溢出的材料。污染物 转移到可接受的废物容器中。收集所有受污染的吸收 剂,按照第十三部分的说明进行处理。用洗涤剂和水 清洁污染区域,收集所有受污染的洗涤水,妥善处 理。

Section 7- Handling and Storage 第七部分 操作处置与储存		
Handling 操作	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.  拆解、挤压、直接放入火中或高温条件下,电池可能发生爆炸和燃烧。禁止短路或将电池正负极错误的安装在设备中。	
Storage 储存	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children. 储藏于阴凉,干燥,通风处,远离接触会发生反应的材料。存储锁定。放在儿童无法接触的地方。	
Other Precautions 其他要注意的防范措施	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.  万一破裂。按照良好的工业卫生和安全规范进行操作。 避免接触皮肤,眼睛或衣服。使用个人防护设备。	

Section 8 - Exposure Controls/Personal Protection 第八部分 接触控制和个体防护	
Engineering Controls 工程控制	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.
	保证空气流通使空气密度保持在低水平。如果在会生成微粒的情况下使用,应仔细观察 3mg/m³ ACGIH TLV-TWA 3 的吸入量(总量为 10mg/m³)。
Personal Protective Equipment 个人防护设备	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight



sealing safety goggles. Face protection shield.
眼睛和脸部保护:消费者无需使用。如果有接触危险:密封安全护目镜。面部防护罩。
Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.
皮肤和身体防护:消费者无需使用。如果有接触危险:穿戴防护手套和防护服。
Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, 柱 ventilation and evacuation may be required.
呼吸系统防护:正常使用条件下不需要防护设备。如果超过暴露限值或发生刺激,可能需要通风和疏散。

Section 9- Physical and Chemical Properties 第九部分 理化特性			
	Appearance: almost cuboid 外形: 近长方体		
Physical State 物理状态	Color: Black 颜色: 黑色		
	Odour: If leaking, smells of medical ether. 气味:泄漏时,医用乙醚的气味。		
Change in conditio 变化的条件:	Change in condition: 变化的条件:		
pH 酸碱度	Not applicable as supplied. 不适用。		
Flash Point 闪点	Not applicable unless individual components exposed. 除非单个的组件暴露,否则不适用。		
Flammability 易燃度	Not applicable unless individual components exposed. 除非单个的组件暴露,否则不适用。		
Relative density: 相对密度	Not applicable unless individual components exposed. 除非单个的组件暴露,否则不适用。		
Solubility (water) 溶解性(水溶性)	Not applicable unless individual components exposed. 除非单个的组件暴露,否则不适用。		
Solubility (other) 溶解性(其他)	Not applicable unless individual components exposed. 除非单个的组件暴露,否则不适用。		

Section 10 – Stability and Reactivity 第十部分 稳定性和反应性		
Chemical Stability	Stable under recommended storage conditions.	
化学稳定性	在推荐的储存条件下可以保持稳定。	
Possibility of Hazardous Reactions	None under normal processing.	



危险反应的可能性	正常处理下没有。
Conditions to Avoid 应避免的条件	Exposure to air or moisture over prolonged periods. 暴露在空气中或长时间受潮。
Incompatible materials	Acids, Oxidizing agents, Bases.
不相容材料	酸,氧化剂,碱。
Hazardous Decomposition Products	Carbon oxides.
有危害分解物	二氧化碳。

Section 11 – Toxicological Information 第十一部分 毒理学信息	
Irritation 刺激	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin. 内部物质暴露的情况下,蒸汽烟雾可能对眼睛和皮肤的刺激性。
Sensitization	Not Available.
致敏	不适用。
Reproductive Toxicity	Not Available.
再生毒性	不适用。
Toxicologically Synergistic Materials	Not Available.
协同材料毒理学	不适用。

Section 12-Ecological Information 第十二部分 生态学信息		
General note: 通用信息:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  不允许未稀释或大量的产品接触地下水、水道或污水处理系统。	
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity  化学产品在环境/可能的环境预期的行为的一种生态毒性	Not Available. 不适用。	

Section 13 – Disposal Considerations 第十三部分 废弃处置	
Waste Treatment 废弃处置方法	Recycle or dispose of in accordance with government, state & local regulations. 建议遵照国家和地方法规处置或再利用。



## Attention for Waste Treatment

废弃注意事项

Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

废电池不能被当作普通垃圾。不能扔进火中或置于高温下。不能解体,刺穿,破碎或类似的处理。最好的 处理办法是回收利用。

Section 14 – Transport Information 第十四部分 运输信息		
UN number 联合国货物编号(UN 编号)	3480 & 3481	
Proper shipping name 运输专用名称	UN3480-Lithium ion batteries (PI 965) UN3480-锂离子电池组 (PI 965) UN3481- Lithium ion Batteries packed with equipment (PI 966) UN3481-电锂离子电池与设备包装在一起 (PI 966) UN3481-Lithium ion Batteries Contained In Equipmen (PI 967) UN3481-锂离子电池安装在设备中 (PI 967)	
Label(s) / Placard Required 标签/标牌要求	Miscellaneous Lithium batt 杂项锂电池	9
Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises.  无论是对内还是对外的运输或运输方式,用户都需要注意或遵守的特殊预防措施。		
ICAO / IATA: 国际民间航空组织/国际航空运输协会:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB、(PI) 966、967 Section II of IATA DGR 64th (2023 Edition) for transportation.  可根据民用航空组织(ICAO),TI 或国际航空运输协会(IATA),DGR 64th(2023 版)包装说明(PI) 965 Section IB、(PI) 966、967 Section II 相关规定进行空运。	
IMDG CODE: 国际海运危险货物规则:	Shipping may be done in accordance with the IMDG Code 2022 Edition (Amdt 41-22). 可根据 IMDG Code 2022 版(Amdt 41-22)相关规定进行海运。	
DOT: 美国运输部:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185. 美国运输部(DOT)有害物质规则 C 分章中的其他规定,运输符合要求 49 CFR 173.185。	
ADR/ ADN: 欧洲国际陆运危险货物协定/关于内陆水道国际运输危险货物的欧洲协定:	Transport Requirements for United Nations Economic Commission for Europe (UNECE) ADR/ADN, Applicable as from 1 January 2024. 自 2024 年 1 月 1 日起需符合联合国欧洲经济委员会(UNECE)ADR / ADN 的运输要求。	
RID: 国际危险货物铁路运输欧洲协定	Regulations concerning the International Carriage of Dangerous Goods by Rail under Special Provision 188	



《国际危险货物铁路运输欧洲协定》(RID)根据特殊规定 188

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

此外,每个锂电芯和电池类型都必须通过联合国《关于危险货物运输的建议书 试验和标准手册》第38.3节规定的适用测试。

## Section 15 - Regulatory Information

第十五部分 法规信息

**Dangerous Goods Regulations** 

《危险物品规则》

Recommendations on the Transport of Dangerous Goods-Model Regulations (23<sup>nd</sup> revised edition)

联合国《关于危险货物运输的建议书规章范本》(23nd修订版)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

联合国《关于危险货物运输的建议书 试验和标准手册》

International Air Transport Association (IATA)

《国际航空运输协会》(IATA)

International Maritime Dangerous Goods (IMDG Code 2022 Edition Amdt 41-22)

《国际海运危险货物规则》(IMDG Code 2022 版 Amdt 41-22)

Technical Instructions for the Safe Transport of Dangerous Goods

《危险货物安全运输技术指南》

Classification and code of dangerous goods (GB 6944-2012)

《危险货物分类和品名编号》- GB 6944-2012

2012《职业安全与健康标准》危险通信标准(29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

《有毒物质控制法》 (TSCA)

Code of Federal Regulations

《联邦条例》

In accordance with all Federal, State and local laws

符合所有联邦、州和地方法律



## Section 16 - Additional Information

第十六部分 其他信息

MSDS creation date: 2024 Version: 1.0

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

本份 MSDS 中的信息只是基于我们当前所拥有的相关材料的信息而编制的,只是为了描述本品的健康、安全与环境需求,以使各有关方面能更好地了解和信任本产品。这些信息只是提供给您,以供考虑、研究和确认。其中的一些危害预防措施描述并非是唯一的。所以本份 MSDS 不能作为使用本品实现任何特定目的的保证。各有关使用者有责任预先完成本品的安全性及其他方面的测试,以评判其是否满足您的使用目的。

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

本文所包含的数据/信息已经过审核和批准,但本文档不包含出口管制信息。

\*\*\*\*\*\*End of report\*\*\*\*\*\*
\*\*\*\*\*\*\*报告结束\*\*\*\*\*\*